
THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NO.	WEIGHT (APPROX.)
NK5EPPG24Y	1.25 lb (567 g)

NOTES:

1. MATERIAL:
   PANEL HOUSING: STEEL
   RJ45 MODULE: THERMOPLASTIC RESIN UL94V-0
   PUNCHDOWN BLOCKS: THERMOPLASTIC RESIN UL94V-0
   BEZEL ASSEMBLY: THERMOPLASTIC RESIN UL94H-B
   RETENTION CAP: THERMOPLASTIC RESIN UL94V-0
2. 24 PORT PATCH PANEL 8 POSITION 8 WIRE.
3. THE PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS.
4. FOUR (4) 12-24 X 1/2" ROUND HEAD SCREWS AND (4) METRIC M6x1x15MM SCREWS ARE PROVIDED FOR FASTENING TO RACKS.
5. DIMENSIONS IN PARENTHESES ARE IN METRIC.
6. USE 110 STYLE TERMINATION TOOL FOR PUNCH DOWN.
7. RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS.

MODEL FILENAME: M02088AA_1RU_24PORT_PANEL_ASSY_06

DRAWING FILENAME: M02479JN_DC250_00A

SIZE: A

TITLE: NETKEY CAT5e 24 PORT PATCH PANEL CUSTOMER DRAWING

PANDUIT™ CORP.
TINLEY PARK, IL 60477

I.I. NUMBER

PRODUCT SPEC

WORK INSTRUCTION

THIRD ANGLE PROJECTION

ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED.
DIMENSIONAL TOLERANCES ARE:
(.X) ± .03 (.XXX) ± .005
(.XX) ± .01 ANGLES ± 1°

SCALE: .25:1

DRAWN BY: LZ

DATE: 3-4-06

CHK'D

REVIEW DRAWING NUMBERS

PART NO.: SEE CHART

DRAWING NO.: 02479-250

REV	DATE	BY	CHK	DESCRIPTION	ECN - R		CUST	SUP	OTH
R	3-4-06	LZ		RELEASED TO PRODUCTION	02479-250				